

MP 567 - Specifiche tecniche



Description

MP 567 è uno pneumatico agro-industriale idoneo per il trasporto sia su campo che su strada, per operazioni nell'ambito municipalità/manutenzione. È lo pneumatico perfetto per sollevatori telescopici e attrezzi agricoli. Lo pneumatico MP 567 offre ottima trazione in tutte le condizioni atmosferiche, nonché delle eccellenti proprietà di autopulitura. Questo pneumatico garantisce un'esperienza di guida confortevole nonché una vita operativa prolungata.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Sollevatore telescopico
Industriale: Sollevatore telescopico • Veicolo universale

Version	IMPLEMENT
Type	TL
Tyre Size	12.0/75 - 18 (300/75 - 18)
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94067541
Ply Rating	12
Section Width (inch)	11.7
Overall Diameter (inch)	36
Static Loaded Radius (inch)	16.8
Rolling Circumference (inch)	107.2
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-006701

Load capacity (lbs)

mph / psi	58
25 FR	5360
25 DW	3740

Printed on 20/04/2024 06:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..