

## MP 567 - Specifiche tecniche



### Description

MP 567 è uno pneumatico agro-industriale idoneo per il trasporto sia su campo che su strada, per operazioni nell'ambito municipalità/manutenzione. È lo pneumatico perfetto per sollevatori telescopici e attrezzi agricoli. Lo pneumatico MP 567 offre ottima trazione in tutte le condizioni atmosferiche, nonché delle eccellenti proprietà di autopulitura. Questo pneumatico garantisce un'esperienza di guida confortevole nonché una vita operativa prolungata.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Sollevatore telescopico  
Industriale: Sollevatore telescopico • Veicolo universale

|           |           |
|-----------|-----------|
| Version   | HD        |
| Type      | TL        |
| Tyre Size | 14.5 - 20 |

## Dimensions International Standard

|                                   |        |
|-----------------------------------|--------|
| <b>Ply Rating</b>                 | 14     |
| <b>Section Width (mm)</b>         | 360    |
| <b>Overall Diameter (mm)</b>      | 1116   |
| <b>Static Loaded Radius (mm)</b>  | 495    |
| <b>Rolling Circumference (mm)</b> | 3315   |
| <b>Rim Rec</b>                    | 11     |
| <b>Rim Alt</b>                    | 12 SDC |

## Load capacity (Kg)

|  | km/h / bar | 3.50 |
|--|------------|------|
|  | 90         | 2430 |
|  | 40         | 2790 |

Printed on 20/04/2024 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..