

MP 585 - Specifiche tecniche



Description

MP 585 è uno pneumatico agro-industriale idoneo per veicoli polivalenti nelle applicazioni municipalità/manutenzione. Lo pneumatico è stato specificamente progettato con un design a blocchi del battistrada che offre massima stabilità e durabilità nelle condizioni operative più difficili, anche ad alte velocità.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo universale
Industriale: Veicolo universale

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	38 A8

Dimensions US Standard

Usa code	94051243
Ply Rating	10
Section Width (inch)	7.9
Overall Diameter (inch)	34.4
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004308

Load capacity (lbs)

mph / psi	80
25	1650

Printed on 06/05/2024 18:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..