MP 590 - Specifiche tecniche

Description

MP 590 è uno pneumatico agro-industriale per operazioni di carico con sollevatori telescopici e carrelli elevatori. Lo pneumatico offre ottima trazione e stabilità eccellente insieme a durabilità superiore.

UM

International Standard

Construction

BIAS

Machinery

Agricoltura: Sollevatore telescopico
Industriale: Carrello elevatore • Sollevatore telescopico • Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

Dimensions International Standard

Ply Rating	20
Section Width (mm)	480
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3534
Rim Rec	14.0
ECE	E11-106R-004408

Load capacity (Kg)

km/h / bar	7.50
40 DW	5800
30 DW	6500

Printed on 05/05/2024 22:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..