

## MT 612 - Specifiche tecniche



### Description

MT 612 è stato sviluppato per impieghi polivalenti su strada e fuoristrada. La carcassa robusta consente il trasporto di carichi pesanti ad alta velocità, mentre i ramponi larghi assicurano straordinaria trazione. Il battistrada extra largo garantisce eccellenti proprietà di galleggiamento su sabbia e fango.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Rimorchio

Industriale: Veicolo universale

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

## Dimensions US Standard

Usa code	94029105
Ply Rating	18
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10

## Load capacity (lbs)

mph / psi	96
50 LS	9920
50 LD	8820

Printed on 25/04/2024 20:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..