

MT 612 - Specifiche tecniche



Description

MT 612 è stato sviluppato per impieghi polivalenti su strada e fuoristrada. La carcassa robusta consente il trasporto di carichi pesanti ad alta velocità, mentre i ramponi larghi assicurano straordinaria trazione. Il battistrada extra largo garantisce eccellenti proprietà di galleggiamento su sabbia e fango.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Veicolo universale

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 14.00 - 20 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94029433 |
| Ply Rating | 20 |
| Section Width (inch) | 15.4 |
| Overall Diameter (inch) | 49.8 |
| Static Loaded Radius (inch) | 23.4 |
| Rolling Circumference (inch) | 150.7 |
| Rim Rec | 10 |
| ECE | E11-54R-0021125 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 110 |
| 50 LS | 10750 |
| 50 LD | 9640 |

Printed on 25/04/2024 23:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..