

MULTIMAX MP 513 - Specifiche tecniche



Description

MULTIMAX MP 513 è stato progettato da BKT per applicazioni con veicoli polivalenti nel settore municipalità/manutenzione e trasporto, sia per uso agricolo che industriale. Lo pneumatico è ideale per veicoli universali ed i camion di fertilizzante. Grazie alla carcassa robusta in nylon rinforzata con cinture in acciaio, MULTIMAX MP 513 consente il trasporto di carichi pesanti ad alte velocità, fornendo un'esperienza di guida confortevole. Garantisce inoltre una maggiore durabilità e trazione nonché eccezionali proprietà di autopulitura.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti
Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	285/80 R 16 MPT
LI/SS	128 G

Dimensions International Standard

Section Width (mm)	304
Overall Diameter (mm)	866
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2617
Rim Rec	W 10
ECE	E11-54R-0020958

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	840	985	1180	1360	1540	1800
65	905	1065	1270	1465	1660	1945
40	965	1135	1355	1560	1770	2070

Printed on 25/04/2024 15:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..