

MULTIMAX MP 513 - Specifiche tecniche



Description

MULTIMAX MP 513 è stato progettato da BKT per applicazioni con veicoli polivalenti nel settore municipalità/manutenzione e trasporto, sia per uso agricolo che industriale. Lo pneumatico è ideale per veicoli universali ed i camion di fertilizzante. Grazie alla carcassa robusta in nylon rinforzata con cinture in acciaio, MULTIMAX MP 513 consente il trasporto di carichi pesanti ad alte velocità, fornendo un'esperienza di guida confortevole. Garantisce inoltre una maggiore durabilità e trazione nonché eccezionali proprietà di autopulitura.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti
Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	365/70 R 18 MPT
LI/SS	133 G

Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	969
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2954
SRI (mm)	475
Rim Rec	11
Rim Alt	11 SDC ; 12 ; 12 SDC
ECE	E11-54R-0016138

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	3.75
90	1080	1280	1520	1760	2000	2060
65	1170	1380	1650	1910	2170	2240
40	1250	1470	1750	2020	2300	2370

Printed on 25/04/2024 23:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..