

MULTIMAX MP 513 - Specifiche tecniche



Description

MULTIMAX MP 513 è stato progettato da BKT per applicazioni con veicoli polivalenti nel settore municipalità/manutenzione e trasporto, sia per uso agricolo che industriale. Lo pneumatico è ideale per veicoli universali ed i camion di fertilizzante. Grazie alla carcassa robusta in nylon rinforzata con cinture in acciaio, MULTIMAX MP 513 consente il trasporto di carichi pesanti ad alte velocità, fornendo un'esperienza di guida confortevole. Garantisce inoltre una maggiore durabilità e trazione nonché eccezionali proprietà di autopulitura.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti
Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	375/70 R 20 MPT
LI/SS	136 G

Dimensions International Standard

Section Width (mm)	377
Overall Diameter (mm)	1034
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3121
Rim Rec	12
Rim Alt	W 10 ; DW 10 ; 11 ; 11 SDC ; W 11 ; DW 11 ; 12 SDC
ECE	E11-54R-0016139

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1210	1435	1705	1975	2240
65	1315	1560	1855	2145	2435
40	1395	1655	1965	2275	2580

Printed on 25/04/2024 16:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..