

## MULTIMAX MP 513 - Specifiche tecniche



### Description

MULTIMAX MP 513 è stato progettato da BKT per applicazioni con veicoli polivalenti nel settore municipalità/manutenzione e trasporto, sia per uso agricolo che industriale. Lo pneumatico è ideale per veicoli universali ed i camion di fertilizzante. Grazie alla carcassa robusta in nylon rinforzata con cinture in acciaio, MULTIMAX MP 513 consente il trasporto di carichi pesanti ad alte velocità, fornendo un'esperienza di guida confortevole. Garantisce inoltre una maggiore durabilità e trazione nonché eccezionali proprietà di autopulitura.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti  
Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	425/55 R 17 MPT
LI/SS	134 G

## Dimensions US Standard

Usa code	94038411
Section Width (inch)	16.6
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	106.1
Rim Rec	13
Rim Alt	13.00
ECE	E4-54R-0024098

## Load capacity (lbs)

mph / psi	23	29	36	44	51
55	2380	2820	3420	4030	4670
40	2590	3060	3710	4390	5080
25	2740	3250	3940	4640	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/10/2024 23:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..