

MULTIMAX MP 515 - Specifiche tecniche



Description

MULTIMAX MP 515 è uno pneumatico radiale agro-industriale, sviluppato per veicoli universali e autocarri per fertilizzanti. È molto idoneo per applicazioni comunali e di trasporto. Lo pneumatico mostra un disegno unico del battistrada che si traduce in ottimo comfort di guida su strada nonché eccezionali qualità di autopulitura e trazione eccellente. La carcassa robusta in nylon con cinture in acciaio e la spalla rinforzata assicurano straordinaria durabilità. MULTIMAX MP 515 è lo pneumatico ideale anche a velocità elevate (90 km/h).

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	493
Rolling Circumference (mm)	3286
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC ; 11 SDC ; 11
ECE	E4-54R-0016565

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1340	1580	1820	2040	2240
65	1455	1715	1975	2215	2435
40	1545	1820	2095	2350	2580

Printed on 27/04/2024 20:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..