

## MULTIMAX MP 515 - Specifiche tecniche



### Description

MULTIMAX MP 515 è uno pneumatico radiale agro-industriale, sviluppato per veicoli universali e autocarri per fertilizzanti. È molto idoneo per applicazioni comunali e di trasporto. Lo pneumatico mostra un disegno unico del battistrada che si traduce in ottimo comfort di guida su strada nonché eccezionali qualità di autopulitura e trazione eccellente. La carcassa robusta in nylon con cinture in acciaio e la spalla rinforzata assicurano straordinaria durabilità. MULTIMAX MP 515 è lo pneumatico ideale anche a velocità elevate (90 km/h).

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

## Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	1146
Static Loaded Radius (mm)	522
Rolling Circumference (mm)	3491
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0017872

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	1540	1810	2150	2490	2820	3150
65	1675	1965	2335	2705	3060	3420
40	1775	2085	2475	2865	3245	3625

Printed on 28/04/2024 01:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..