

MULTIMAX MP 515 - Specifiche tecniche



Description

MULTIMAX MP 515 è uno pneumatico radiale agro-industriale, sviluppato per veicoli universali e autocarri per fertilizzanti. È molto idoneo per applicazioni comunali e di trasporto. Lo pneumatico mostra un disegno unico del battistrada che si traduce in ottimo comfort di guida su strada nonché eccezionali qualità di autopulitura e trazione eccellente. La carcassa robusta in nylon con cinture in acciaio e la spalla rinforzata assicurano straordinaria durabilità. MULTIMAX MP 515 è lo pneumatico ideale anche a velocità elevate (90 km/h).

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

Dimensions US Standard

Usa code	94055975
Section Width (inch)	16.6
Overall Diameter (inch)	45.1
Static Loaded Radius (inch)	20.6
Rolling Circumference (inch)	137.4
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0017872

Load capacity (lbs)

mph / psi	23	29	36	44	51	58
55	3390	3990	4740	5490	6220	6940
40	3690	4330	5150	5960	6750	7540
25	3910	4600	5460	6320	7150	7990

Printed on 27/04/2024 23:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..