

## MULTIMAX MP 515 - Scheda tecnica



### Description

MULTIMAX MP 515 è uno pneumatico radiale agro-industriale, sviluppato per veicoli universali e autocarri per fertilizzanti. È molto idoneo per applicazioni comunali e di trasporto. Lo pneumatico mostra un disegno unico del battistrada che si traduce in ottimo comfort di guida su strada nonché eccezionali qualità di autopulitura e trazione eccellente. La carcassa robusta in nylon con cinture in acciaio e la spalla rinforzata assicurano straordinaria durabilità. MULTIMAX MP 515 è lo pneumatico ideale anche a velocità elevate (90 km/h).

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>405/70 R 20 MPT</b>	STANDARD	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	407	1076	493	3286	TL	E4-54R-0016565
<b>425/75 R 20 MPT</b>	STANDARD	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	421	1146	522	3491	TL	E11-54R-0017872
<b>445/65 R 22.5 MPT</b>	STANDARD	160 G	13	14	444	1150	527	3532	TL	E11-54R-0017868

Printed on 27/04/2024 20:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..