

MULTIMAX MP 519 - Specifiche tecniche



Description

MULTIMAX MP 519 è uno pneumatico particolarmente idoneo per autocarri leggeri in tutte le applicazioni di trasporto. La carcassa rinforzata con cinture in acciaio garantisce eccellente stabilità a velocità elevate (90 km/h). Grazie alla bassa resistenza di rotolamento, lo pneumatico assicura una riduzione nei consumi di carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Autocarro leggero

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	112/110G

Dimensions US Standard

Usa code	94063437
Ply Rating	8
Section Width (inch)	8.7
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	96.4
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L
ECE	E11-54R-0019046

Load capacity (lbs)

mph / psi	51
55 LS	2470
55 LD	2340

Printed on 25/04/2024 18:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..