

## MULTIMAX MP 525 - Specifiche tecniche



### Description

MULTIMAX MP 525 è uno pneumatico radiale All Steel polivalente, progettato per sollevatori telescopici, pale compatte e motolivellatrici in applicazioni agroindustriali. Lo pneumatico è stato sviluppato appositamente per trasportare carichi pesanti a velocità elevate sia su strada che fuori strada. Infatti, l'ampio disegno non direzionale del battistrada offre una trazione eccellente su qualsiasi superficie, oltre a eccezionali proprietà autopulenti. Il robusto fianco assicura straordinaria stabilità laterale in modalità di sollevamento, rendendolo la scelta ideale per le operazioni agricole e per la movimentazione dei materiali. MULTIMAX MP 525 è realizzato con una mescola del battistrada particolarmente resistente a tagli e strappi che si traduce in una maggiore vita operativa dello pneumatico grazie alla sua straordinaria resistenza a qualsiasi tipo di taglio e foratura.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Pala compatta • Motolivellatrice • Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 (16.0/70 R 20)
LI/SS	152 J/168 A2

## Dimensions US Standard

Usa code	94072873
Overall Width (inch)	15.9
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128.3
Rim Rec	13
Rim Alt	12; 13 SDC
ECE	E11-54R-0020576

## Load capacity (lbs)

mph / psi	87
62	7830
5	12350

Printed on 02/05/2024 04:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..