

## MULTIMAX MP 527 - Scheda tecnica



### Description

MULTIMAX MP 527 è uno pneumatico radiale polivalente sviluppato per sollevatori telescopici e pale compatte nelle applicazioni agro-industriali. Lo pneumatico è dotato di un disegno a blocchi del battistrada che garantisce eccellente trazione anche sulle superfici più dure. Il fianco robusto dello pneumatico assicura straordinaria stabilità in modalità di sollevamento. MULTIMAX MP 527 è realizzato con una mescola particolarmente resistente a tagli e lacerazioni che si traduce in una lunga vita operativa dello pneumatico.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Pala compatta • Sollevatore telescopico  
Industriale: Pala compatta • Sollevatore telescopico

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>340/80 R 18 IND</b>	STANDARD	143 A8/B	11; 11 SDC; W 11	W 10; 12; 12 SDC	343	1001	455	3028	475	TL	E4-106R-002981
<b>360/70 R 18 IND</b>	STANDARD	142 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	360	969	439	2887	475	TL	E11-106R-002996
<b>340/80 R 20 IND</b>	STANDARD	144 A8/B	11	W10; 11 SDC; W11; 12; 12 SDC	343	1052	483	3176	500	TL	E11-106R-003957
<b>400/70 R 20 IND (16.0/70 R 20)</b>	STANDARD	149 A8/B	13	12 SDC; 13 SDC; 14	404	1068	494	3282	525	TL	E4-106R-002656
<b>400/70 R 24 IND</b>	STANDARD	152 A8/B	13	DW 12; DW 13; DW 13 L; 13 SDC; DW 14 L	404	1170	542	3597	575	TL	E11-106R-003958
<b>400/80 R 24 IND</b>	STANDARD	162 A8/B	DW 13	DW 12; DW 13 L; DW 14 L	404	1250	578	3834	600	TL	E11-106R-002982
<b>440/80 R 24 IND</b>	STANDARD	161 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1314	601	3985	625	TL	E4-106R-002657
<b>460/70 R 24 IND (17.5L R 24)</b>	STANDARD	159 A8/B	DW 15 L	DW 14 L; DW 16 L	465	1254	574	3801	600	TL	E11-106R-002983
<b>500/70 R 24 IND</b>	STANDARD	164 A8/B	DW 16 L	DW 15 L; DW 18 L	503	1310	597	4019	625	TL	E4-106R-002658
<b>480/80 R 26 IND</b>	STANDARD	160 A8/B	DW 15 L	DW 16 L	479	1428	642	4259	675	TL	E11-106R-004069
<b>440/80 R 28 IND</b>	STANDARD	156 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1415	648	4270	675	TL	E11-106R-002984

Printed on 26/04/2024 12:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..