

MULTIMAX MP 529 - Specifiche tecniche



Description

MULTIMAX MP 529 è uno pneumatico radiale multiuso con cinture in acciaio sviluppato per sollevatori telescopici nelle applicazioni industriali. Il disegno del battistrada è stato sviluppato appositamente per superfici dure. Il fianco robusto dello pneumatico e un'impronta a terra più larga assicurano straordinaria stabilità in modalità di sollevamento. MULTIMAX MP 529 si distingue inoltre per la carcassa robusta resistente alla foratura ed è realizzato con una mescola particolarmente resistente ai tagli e strappi che si traducono in durabilità elevata e in una lunga vita operativa dello pneumatico.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18
LI/SS	143 A8/B

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1001
Static Loaded Radius (mm)	445
Rolling Circumference (mm)	3007
SRI (mm)	475
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002972

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 Cyc.	1600	1965	2315	2660	3030	3295	3725	3930	4090
Static	2450	3010	3545	4080	4640	5050	5710	6020	6270

Printed on 26/04/2024 23:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..