

## MULTIMAX MP 538 - Specifiche tecniche



### Description

MULTIMAX MP 538 è uno pneumatico radiale multiuso progettato specificamente per diversi macchinari e applicazioni: motolivellatrici e pale cariatrici operanti in condizioni invernali, nonché sollevatori telescopici, veicoli universali e spazzatrici per la manutenzione stradale. Grazie alla robusta carcassa con cintura d'acciaio, MULTIMAX MP 538 consente di trasportare carichi pesanti anche a velocità elevate. Inoltre, il suo esclusivo design del battistrada contribuisce a mantenere un'eccellente trazione su ghiaccio e neve.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Sollevatore telescopico • Veicolo universale  
Industriale: Motolivellatrice • Pala cariatrica

|           |                 |
|-----------|-----------------|
| Version   | STEEL BELTED    |
| Type      | TL              |
| Tyre Size | 405/70 R 20 MPT |
| LI/SS     | 152 G           |

## Dimensions International Standard

|                            |      |
|----------------------------|------|
| Section Width (mm)         | 407  |
| Overall Diameter (mm)      | 1076 |
| Static Loaded Radius (mm)  | 484  |
| Rolling Circumference (mm) | 3289 |
| Rim Rec                    | W13  |

## Load capacity (Kg)

| km/h / bar | 6    |
|------------|------|
| 90         | 3550 |
| 65         | 3850 |
| 40         | 4080 |

Printed on 29/04/2024 06:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..