

MULTIMAX MP 538 - Scheda tecnica



Description

MULTIMAX MP 538 è uno pneumatico radiale multiuso progettato specificamente per diversi macchinari e applicazioni: motolivellatrici e pale cariatrici operanti in condizioni invernali, nonché sollevatori telescopici, veicoli universali e spazzatrici per la manutenzione stradale. Grazie alla robusta carcassa con cintura d'acciaio, MULTIMAX MP 538 consente di trasportare carichi pesanti anche a velocità elevate. Inoltre, il suo esclusivo design del battistrada contribuisce a mantenere un'eccellente trazione su ghiaccio e neve.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Sollevatore telescopico • Veicolo universale
Industriale: Motolivellatrice • Pala cariatrica

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
405/70 R 20 MPT	STEEL BELTED	152 G	W13		407	1076	484	3289	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 15:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..