

MULTIMAX MP 569 - Scheda tecnica



Description

Il nuovo pneumatico MULTIMAX MP 569 è specificamente progettato per i camion agricoli. È la soluzione innovativa che migliora le prestazioni sia del trattore sia del camion, al fine di soddisfare le esigenze specifiche dell'agricoltura moderna in diverse applicazioni. Grazie alla carcassa interamente in acciaio, lo pneumatico si distingue per la sua capacità di alta velocità e durata elevata.

Il disegno ottimizzato del battistrada fornisce una maggiore trazione sul campo e grandi proprietà autopulenti, insieme a una guida estremamente confortevole e stabile su strada. Senza contare che MULTIMAX MP 569 assicura un notevole risparmio di carburante grazie ad una bassa resistenza al rotolamento.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Sollevatore telescopico • Camion agricolo
Industriale: Sollevatore telescopico

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
445/65 R 22.5 (18 R 22.5)	STANDARD	169 J	13.00	14.00	440	1174	528	3558	TL	E11-54R-0019094

Printed on 20/04/2024 17:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..