

MULTIMAX MP 538 - Specifiche tecniche



Description

MULTIMAX MP 538 è uno pneumatico radiale multiuso progettato specificamente per diversi macchinari e applicazioni: motolivellatrici e pale caricatrici operanti in condizioni invernali, nonché sollevatori telescopici, veicoli universali e spazzatrici per la manutenzione stradale. Grazie alla robusta carcassa con cintura d'acciaio, MULTIMAX MP 538 consente di trasportare carichi pesanti anche a velocità elevate. Inoltre, il suo esclusivo design del battistrada contribuisce a mantenere un'eccellente trazione su ghiaccio e neve.

UM

International Standard

Construction

RADIAL

Machinery

Agricoltura: Sollevatore telescopico, Veicolo universale
Industriale: Motolivellatrice, Pala caricatrice

Version	STEEL BELTED
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	152 G

Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	484
Rolling Circumference (mm)	3289
Rim Rec	W13

Load capacity (Kg)

km/h / bar	6
90	3550
65	3850
40	4080

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..