

PAC MASTER - Specifiche tecniche



Description

PAC MASTER è un pneumatico diagonale per compattatori. Fornisce elevata stabilità e assicura un ciclo di vita prolungato. Lo pneumatico è realizzato con una miscela speciale che fornisce particolare resistenza al calore.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Compattatore

Version	SPECIAL
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94067169
Ply Rating	18
Section Width (inch)	11.5
Overall Diameter (inch)	42.1
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	130.3
Rim Rec	8.0
Rim Alt	8.5
ECE	E11-106R-006177

Load capacity (lbs)

mph / psi	120
5	12800
10	10200

Printed on 24/04/2024 22:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..