PAC MASTER - Specifiche tecniche

Description

PAC MASTERè uno pneumatico diagonale per compattatori. Fornisce elevata stabilità e assicura un ciclo di vita prolungato. Lo pneumatico è realizzato con una mescola speciale che fornisce particolare resistenza al calore.

UM

US Standard

Construction

BIAS

Machinery

Industriale: Compattatore

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

Dimensions US Standard

Usa code	94002542
Ply Rating	6
Section Width (inch)	8.9
Overall Diameter (inch)	31.1
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005269

Load capacity (lbs)

mph / psi	58
5	4080
10	3310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 11:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..