

PAC MASTER - Specifiche tecniche



Description

PAC MASTER è un pneumatico diagonale per compattatori. Fornisce elevata stabilità e assicura un ciclo di vita prolungato. Lo pneumatico è realizzato con una miscela speciale che fornisce particolare resistenza al calore.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Compattatore

Version	STANDARD
Type	TL
Tyre Size	8.5/90 - 15 K

Dimensions International Standard

Ply Rating	6
Section Width (mm)	230
Overall Diameter (mm)	785
Rim Rec	6.0
Rim Alt	5.50 F
ECE	E11-106R-003530

Load capacity (Kg)

km/h / bar	3.50
10	1800
15	1450

Printed on 24/04/2024 22:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..