

PAC MASTER - Specifiche tecniche



Description

PAC MASTER è un pneumatico diagonale per compattatori. Fornisce elevata stabilità e assicura un ciclo di vita prolungato. Lo pneumatico è realizzato con una miscela speciale che fornisce particolare resistenza al calore.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Compattatore

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	275
Overall Diameter (mm)	1016
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3107
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005360

Load capacity (Kg)

km/h / bar	8.25
10	4750
15	3750

Printed on 25/04/2024 00:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..