

PL 801 - Specifiche tecniche



Description

PL 801 è stato particolarmente sviluppato per applicazioni con ranghinatori rotativi e spandivoltafieno nonché per operazioni logistiche con carrelli elevatori. Lo pneumatico offre eccellente stabilità insieme ad elevata resistenza ad ogni tipo di taglio. PL 801 assicura un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia • Ranghinatore • Carrello
elevatore

Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	18 X 7 - 8 (180/70 - 8)

Dimensions International Standard

Ply Rating	14
Section Width (mm)	173
Overall Diameter (mm)	470
Rim Rec	4.33 R
Rim Alt	5.00 F

Load capacity (Kg)

	km/h / bar	9.00
25 LOAD WHEEL		1885
25 STEER WHEEL		1450
10 OTHER VEHICLES		1885
25 OTHER VEHICLES		1450
STATIC SIDE LOADER		2190

Printed on 23/04/2024 18:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..