

## PL 801 - Specifiche tecniche



### Description

PL 801 è stato particolarmente sviluppato per applicazioni con ranghinatori rotativi e spandivoltafieno nonché per operazioni logistiche con carrelli elevatori. Lo pneumatico offre eccellente stabilità insieme ad elevata resistenza ad ogni tipo di taglio. PL 801 assicura un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Mietitrebbia • Ranghinatore • Carrello  
elevatore

Industriale: Carrello elevatore

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TT                         |
| Tyre Size | 18 X 7 - 8<br>(180/70 - 8) |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94006953 |
| Ply Rating              | 14       |
| Section Width (inch)    | 6.8      |
| Overall Diameter (inch) | 18.5     |
| Rim Rec                 | 4.33 R   |
| Rim Alt                 | 5.00 F   |

## Load capacity (lbs)

|                    | mph / psi | 131  |
|--------------------|-----------|------|
| 15 LOAD WHEEL      |           | 4155 |
| 15 STEER WHEEL     |           | 3195 |
| 5 OTHER VEHICLES   |           | 4155 |
| 15 OTHER VEHICLES  |           | 3195 |
| STATIC SIDE LOADER |           | 4830 |

Printed on 23/04/2024 17:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..