

PL 801 - Specifiche tecniche



Description

PL 801 è stato particolarmente sviluppato per applicazioni con ranghinatori rotativi e spandivoltafieno nonché per operazioni logistiche con carrelli elevatori. Lo pneumatico offre eccellente stabilità insieme ad elevata resistenza ad ogni tipo di taglio. PL 801 assicura un ciclo di vita prolungato dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia • Ranghinatore • Carrello
elevatore

Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	5.50 - 15

Dimensions US Standard

Usa code	94030545
Ply Rating	8
Section Width (inch)	6.2
Overall Diameter (inch)	26.4
Rim Rec	4.50 E DT
Rim Alt	4.50 E SDC

Load capacity (lbs)

mph / psi	106
15 LOAD WHEEL	4300
15 STEER WHEEL	3185
5 OTHER VEHICLES	4300
15 OTHER VEHICLES	3185
STATIC SIDE LOADER	4805

Printed on 23/04/2024 18:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..