

## PL 846 - Specifiche tecniche



### Description

PL 846 è stato particolarmente progettato per attrezzi agricoli nelle applicazioni per la lavorazione della terra. Lo pneumatico offre straordinaria stabilità ed eccezionale trazione insieme ad un'elevata resistenza ad ogni tipo di taglio. PL 846 è lo pneumatico ideale su superfici rocciose.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	160
<b>Overall Diameter (mm)</b>	540
<b>Rim Rec</b>	4.00 E

## Load capacity (Kg)

km/h / bar	8.50
25	1320

Printed on 19/04/2024 04:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..