

PORT KING CLASSIC - Specifiche tecniche



Description

PORT KING CLASSIC è lo pneumatico portuale BKT di ultima generazione, particolarmente studiato per veicoli per la movimentazione di container. Lo pneumatico assicura massima efficienza operativa e stabilità eccezionale in modalità di sollevamento. Grazie alla sua robusta carcassa in nylon, PORT KING CLASSIC si distingue per una maggiore capacità di carico, minimizzando il rischio di rotture da impatto, lacerazioni e perforazioni. La nuova miscela resistente all'usura è stata sviluppata per assicurare un ciclo di vita prolungato del prodotto e garantire il migliore ritorno sull'investimento.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94054480
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	195.1
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	50625

Printed on 28/04/2024 22:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..