

POWER TRAX HD SMOOTH - Specifiche tecniche



Description

POWER TRAX HD SMOOTH è uno pneumatico a tele incrociate specificamente sviluppato per operazioni portuali e nelle miniere sotterranee. La particolare protezione del fianco, insieme al battistrada solido, evita danni da tagli e perforazioni, piuttosto comuni in questi ambienti esigenti. Se dovete spostare carichi pesanti in condizioni dure, POWER TRAX HD SMOOTH è lo pneumatico ideale per le vostre esigenze.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container • Carrello elevatore

OTR: Veicolo per miniere sotterranee

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94007882
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-005561

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20350
15 STEER WHEEL	15650
5 OTHER VEHICLES	20350
15 OTHER VEHICLES	15650
STATIC SIDE LOADER	23630

Printed on 24/02/2024 06:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..