

POWER TRAX HD SMOOTH - Specifiche tecniche



Description

POWER TRAX HD SMOOTH è uno pneumatico a tele incrociate specificamente sviluppato per operazioni portuali e nelle miniere sotterranee. La particolare protezione del fianco, insieme al battistrada solido, evita danni da tagli e perforazioni, piuttosto comuni in questi ambienti esigenti. Se dovete spostare carichi pesanti in condizioni dure, POWER TRAX HD SMOOTH è lo pneumatico ideale per le vostre esigenze.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container • Carrello elevatore

OTR: Veicolo per miniere sotterranee

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	28
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	9490
25 STEER WHEEL	7300
10 OTHER VEHICLES	9490
25 OTHER VEHICLES	7300
STATIC SIDE LOADER	11025

Printed on 26/04/2024 09:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..