

POWER TRAX HD (SS) - Specifiche tecniche



Description

Lo pneumatico premium POWER TRAX HD è appositamente progettato per le attrezzature in applicazioni portuali e sotterranee. Il battistrada profondo, la parete laterale extra spessa e il rivestimento resistente offrono una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali. Lo pneumatico presenta un'eccellente resistenza al taglio e ai trucioli, ed è particolarmente adatto per superfici ruvide e dure. La protezione dei cerchioni, appositamente progettata, previene danni alla piana e alle ruote nell'area della flangia del cerchione.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	324
Overall Diameter (mm)	865
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2552
Rim Rec	9.75

Load capacity (Kg)

km/h / bar	4.50
10	2540
15	2005
25	1855

Printed on 27/04/2024 12:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..