

## POWER TRAX - Specifiche tecniche



### Description

POWER TRAX è uno pneumatico premium appositamente progettato per servizi pesanti su rimorchi portuali, movimentatori di container vuoti o ECH e macchinari per miniere sotterranee. Il battistrada profondo e la robusta carcassa assicurano una durata eccezionale, riducendo al minimo il rischio di forature e danni accidentali. POWER TRAX è lo pneumatico ideale per operazioni dure e difficili, grazie all'esclusiva mescola del battistrada che offre un'eccellente resistenza a tagli e scheggiature.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Movimentatore per container vuoti  
OTR: Veicolo per miniere sotterranee

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20
LI/SS	176 A5

## Dimensions US Standard

Usa code	94067701
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.5
Rim Alt	9.0

## Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20350
15 STEER WHEEL	15650
5 OTHER VEHICLES	20350
15 OTHER VEHICLES	15650
STATIC SIDE LOADER	23630

Printed on 27/04/2024 09:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..