

PUDDLE SPECIAL (A) - Specifiche tecniche



Description

PUDDLE SPECIAL è uno pneumatico agricoltura R-2 particolarmente sviluppato per operazioni nelle risaie. Il disegno extra profondo del battistrada, oltre alla disposizione speciale dei ramponi, assicura ottima aderenza e trazione eccellente anche su terreno bagnato e soffice. Il largo elemento centrale offre una migliore capacità di adattamento per applicazioni su strada oltre a eccellenti prestazioni operative. In aggiunta, PUDDLE SPECIAL mostra ottime proprietà di auto-pulitura e durabilità elevata.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	11 - 32
LI/SS	111 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	305
Overall Diameter (mm)	1465
Static Loaded Radius (mm)	702
Rolling Circumference (mm)	4384
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

Load capacity (Kg)

km/h / bar	1.60
10	1090

Printed on 12/08/2024 15:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..