

RIB 775 - Specifiche tecniche



Description

RIB 775 è uno pneumatico a tele incrociate a sezione bassa, idoneo per il trasporto e applicazioni di lavorazione del suolo con rimorchi e attrezzi agricoli. Lo pneumatico offre un'eccellente capacità di carico ed un ciclo di vita lungo del prodotto.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 300/65 - 12 |
| LI/SS FREE ROLLING | 116 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94011049 |
| Ply Rating | 8 |
| Section Width (inch) | 12 |
| Overall Diameter (inch) | 27 |
| Static Loaded Radius (inch) | 12 |
| Rolling Circumference (inch) | 79 |
| Rim Rec | 9.0 |
| ECE | E11-106R-003582 |

Load capacity (lbs)

| mph / psi | 38 |
|-----------|------|
| 5 FR | 3860 |
| 15 FR | 3280 |
| 20 FR | 3090 |
| 25 FR | 2760 |

Printed on 22/04/2024 23:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..