

RIB 900 - Specifiche tecniche



Description

RIB 900 è uno pneumatico idoneo per il trasporto, la lavorazione del terreno nonché la raccolta del fieno con rimorchi, attrezzi agricoli e presse per balle di fieno. Lo pneumatico offre eccellente capacità di carico insieme ad un ciclo di vita prolungato.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/60 - 15.5 |
| LI/SS FREE ROLLING | 145 A8 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 14 |
| Section Width (mm) | 405 |
| Overall Diameter (mm) | 875 |
| Static Loaded Radius (mm) | 380 |
| Rolling Circumference (mm) | 2564 |
| Rim Rec | AG 13.00 |
| ECE | E4-106R-001551 |

Load capacity (Kg)

| | km/h / bar | 3.60 |
|--|------------|------|
| | 10 FR | 4060 |
| | 25 FR | 3450 |
| | 30 FR | 3250 |
| | 40 FR | 2900 |

Printed on 23/04/2024 14:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..