

RIB IMPLEMENT (B) - Specifiche tecniche



Description

RIB IMPLEMENT (B) è stato specificamente progettato per attrezzi agricoli. Questo pneumatico ideale per le aziende agricole moderne è stato realizzato con una miscela resistente alle stoppie, che garantisce un'eccellente protezione contro le forature. RIB IMPLEMENT (B) è uno pneumatico con nervatura del battistrada a 5 costole caratterizzato da una carcassa particolarmente durevole che assicura un ciclo di vita prolungato. È la scelta migliore per qualsiasi condizione d'impiego che richiede alta capacità di carico e bassa resistenza al rotolamento.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions International Standard

Ply Rating	20
Section Width (mm)	425
Overall Diameter (mm)	1200
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (Kg)

km/h / bar	4.0
40 FR	4250
50 FR	3750
40 DW	3000
50 DW	2725

Printed on 28/11/2023 17:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..