

RIB IMPLEMENT (B) - Specifiche tecniche



Description

RIB IMPLEMENT (B) è stato specificamente progettato per attrezzi agricoli. Questo pneumatico ideale per le aziende agricole moderne è stato realizzato con una miscela resistente alle stoppie, che garantisce un'eccellente protezione contro le forature. RIB IMPLEMENT (B) è uno pneumatico con nervatura del battistrada a 5 costole caratterizzato da una carcassa particolarmente durevole che assicura un ciclo di vita prolungato. È la scelta migliore per qualsiasi condizione d'impiego che richiede alta capacità di carico e bassa resistenza al rotolamento.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions US Standard

Usa code	94046591
Ply Rating	20
Section Width (inch)	16.7
Overall Diameter (inch)	47.2
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (lbs)

mph / psi	58
25 FR	9370
30 FR	8270
25 DW	6610
30 DW	6000

Printed on 09/05/2024 12:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..