

RIDEMAX FL 690 - Specifiche tecniche



Description

RIDEMAX FL 690 è uno pneumatico radiale Flotation e di trasporto idoneo per rimorchi e autobotti. È uno pneumatico idoneo per applicazioni 75% su strada. Per rispondere alla domanda di carichi sempre più pesanti nell'agricoltura moderna, BKT ha sviluppato questo pneumatico con cinture in acciaio per renderlo forte e supportare carichi molto pesanti, incrementando la produttività dell'agricoltore. La bassa resistenza al rotolamento contribuisce ad un notevole risparmio di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio
Industriale: Rimorchio

Version	STANDARD
Type	TL
Tyre Size	28L R 26 (750/65 R 26)
LI/SS	176 A8/173 B

Dimensions International Standard

Section Width (mm)	719
Overall Diameter (mm)	1590
Static Loaded Radius (mm)	695
Rolling Circumference (mm)	4745
SRI (mm)	750
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-002985

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8
50	3120	3560	4325	4680	5330	5915	6500
40	3410	3885	4725	5115	5825	6465	7100
30	3820	4355	5295	5730	6525	7240	7955
25	4060	4625	5620	6085	6930	7690	8450
10	4775	5440	6615	7160	8155	9050	9940

Printed on 17/04/2024 23:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..