

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	163 D

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	544
Rolling Circumference (mm)	3625
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-007203

Load capacity (Kg)

km/h / bar	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.5	5	5.5	6.0
70	1470	1825	2000	2310	2620	2890	3155	3465	3690	3910	4175	4440
65	1610	2000	2195	2535	2880	3170	3465	3805	4050	4290	4585	4875
50	1950	2420	2655	3070	3485	3835	4190	4605	4900	5195	5550	5900
40	2190	2720	2985	3450	3915	4310	4710	5175	5505	5835	6235	6630
25	2545	3160	3470	4010	4550	5010	5475	6010	6400	6785	7245	7705
10	2900	3600	3950	4565	5180	5705	6235	6845	7285	7725	8250	8775

Printed on 25/04/2024 21:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..