

## RIDEMAX FL 693 M - Specifiche tecniche



### Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/45 R 22.5
LI/SS	160D

## Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	491
Rolling Circumference (mm)	3306
SRI (mm)	525
Rim Rec	AG 16.00
ECE	E11-106R-009052

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
70	990	1320	1650	1860	2145	2435	2685	2930	3220	3425	3630	3880	4125
65	1080	1440	1800	2025	2340	2655	2925	3195	3510	3735	3960	4230	4500
50	1310	1745	2180	2455	2835	3215	3540	3870	4250	4520	4795	5120	5445
40	1470	1960	2450	2755	3185	3615	3980	4350	4775	5080	5390	5755	6120
30	1635	2175	2720	3060	3535	4010	4420	4825	5305	5640	5980	6390	6795
25	1710	2280	2845	3200	3700	4195	4625	5050	5550	5905	6260	6685	7110
10	1945	2595	3240	3645	4215	4780	5265	5755	6320	6725	7130	7615	8100

Printed on 17/04/2024 18:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..