

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

Dimensions US Standard

Usa code	94066193
Section Width (inch)	21.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	148.3
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E11-106R-006650

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	73	87
45	3850	4770	5250	6060	6880	7570	8270	9080	10250	11640
40	4220	5250	5750	6660	7550	8310	9080	9980	11250	12790
30	5110	6350	6970	8060	9140	10060	10990	12080	13620	15480
25	5740	7130	7840	9050	10270	11310	12360	13570	15310	17390
15	6670	8290	9090	10520	11930	13140	14350	15760	17790	20200
5	7610	9450	10360	11970	13580	14970	16350	17960	20260	23010

Printed on 20/04/2024 22:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..