

## RIDEMAX FL 693 M - Specifiche tecniche



### Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Autobotte • Rimorchio

Version	HD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	178 D

## Dimensions US Standard

Usa code	94049622
Section Width (inch)	25.4
Overall Diameter (inch)	54.7
Static Loaded Radius (inch)	24.2
Rolling Circumference (inch)	167.3
Rim Rec	AG 20.00
ECE	E11-106R-003008

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73	87
40	5130	6120	7440	8600	9920	11240	12070	13390	14720	15540	16530
30	6210	7410	9010	10410	12000	13610	14600	16210	17810	18820	20010
25	6980	8320	10120	11690	13490	15300	16420	18220	20020	21140	22490
20	7750	9250	11240	12980	14980	16990	18230	20230	22220	23480	24970
15	8100	9670	11760	13590	15670	17770	19080	21160	23260	24560	26120
5	9230	11010	13390	15480	17860	20240	21730	24110	26490	27980	29760

Printed on 12/04/2024 15:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..