

## RIDEMAX FL 693 M - Specifiche tecniche



### Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D

## Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4216
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E4-106R-000806

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1965	2230	2705	3130	3605	4085	4400	4880	5300
65	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2920	3315	4025	4660	5370	6080	6550	7260	7890
25	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3865	4385	5325	6160	7100	8040	8670	9605	10440

Printed on 20/04/2024 22:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..