

RIDEMAX IT 696 - Specifiche tecniche



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	440/80 R 24 IND (16.9 R 24)
LI/SS	154 A8/149 D

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1314
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3939
SRI (mm)	625
Rim Rec	DW 14 L
Rim Alt	DW 15 L ; DW 13
ECE	E11-106R-004760

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1530	1885	2210	2570	2895	3250
50	1650	2035	2385	2775	3125	3510
40	1765	2175	2550	2965	3340	3750
30	2115	2610	3060	3555	4005	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/04/2025 04:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..