

## RIDEMAX IT 696 - Specifiche tecniche



### Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	440/80 R 30 IND (16.9 R 30)
LI/SS	157 A8/153 D

## Dimensions US Standard

Usa code	94035816
Section Width (inch)	17.4
Overall Diameter (inch)	57.7
Static Loaded Radius (inch)	26.3
Rolling Circumference (inch)	175.4
Rim Rec	W 14 L
Rim Alt	W 15 L
ECE	E4-106R-002297

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	3780	4660	5470	6360	7160	8050
30	4020	4960	5820	6760	7620	8550
25	4280	5280	6180	7190	8090	9090
20	4450	5500	6450	7480	8430	9480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/04/2025 19:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..