

RIDEMAX IT 696 - Specifiche tecniche



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	500/70 R 24 IND
LI/SS	157 A8/152 D

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	602
Rolling Circumference (mm)	3954
SRI (mm)	625
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-007051

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1775	2170	2380	2805	3160	3550
50	1920	2340	2570	3030	3415	3835
40	2065	2520	2765	3260	3675	4125
30	2130	2600	2855	3370	3795	4260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/04/2025 07:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..