

RIDEMAX IT 696 - Specifiche tecniche



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/70 R 24 IND |
| LI/SS | 157 A8/152 D |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94067862 |
| Section Width (inch) | 19.8 |
| Overall Diameter (inch) | 51.6 |
| Static Loaded Radius (inch) | 23.7 |
| Rolling Circumference (inch) | 155.7 |
| Rim Rec | DW 16 L |
| Rim Alt | DW 15 L ; DW 18 L |
| ECE | E11-106R-007051 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 3910 | 4780 | 5250 | 6180 | 6970 | 7830 |
| 30 | 4230 | 5160 | 5670 | 6680 | 7530 | 8450 |
| 25 | 4550 | 5560 | 6100 | 7190 | 8100 | 9090 |
| 20 | 4700 | 5730 | 6290 | 7430 | 8370 | 9390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/04/2025 19:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..